



STAIR LIFT WITH CHAIR MODEL F2P





STAIR LIFT WITH CHAIR MODEL F2P

The FABOC due stair lift with chair is designed and supplied complete with all the accessories, which make it simple, easy and safe to use. The compact single track blends in easily with the environment in which it is inserted and it is modelled according to the shape of the stairs. The system is suitable for straight and curved routings and also with variable gradients. The seat, backrest and armrests are padded and upholstered in black fabric. The footrest is tiltable to reduce the size of the machine when closed.

In the case of installation outdoors a waterproof canvas is supplied to protect the machine against the weather.

The system is fitted with all the safety systems required by current regulations. The machine can be installed with no need for accessory masonry works or special permit.

Special finishes or accessories can be made on request.



Specifications:

- Capacity: 150 Kg.
- Maximum speed: 6 m/min.
- Single rectangular tubular guide mm 120x60
- Guide size: generally within *200 mm from the wall or railing behind
- Guide height: generally between *300 and *900 mm from the edge of the step
- Closed machine size approx. *450 mm from the wall or railing behind
- Minimum stair width 850 mm
- Seat tiltable and swivelling by 90° to facilitate getting off, with 2 tiltable armrests and safety belt
- Tiltable footrest with non-slip aluminium surface, size: mm 320x300
- Lever controls on armrest protected with security key
- Hand-operated radio control for calling/returning the closed machine (Optional)
- Radio-controlled landing pushbutton strips that do not require connection with the electric system
- 24 VDC supply with batteries on the machine, with anti black-out system incorporated
- Automatic battery charger with sliding contacts at the ends of the track (Supply 220V - Absorption 100W)
- Self-braking 650 W 24 VDC motor
- Tow with toothed pinion and irreversible reduction gear on rack and pinion fastened to the bottom part of the track
- Parachute operated by speed limiting device according to UNI Std. 9801
- Anti-crushing, anti-shearing and antishock systems according to UNI Std. UNI 9801
- Track fastening with feet in bearing steps or connections to bearing wall
- Standard colours: machine RAL 9010 - Track and feet black. Black fabric.



The systems have been designed and manufactured in accordance with the provisions of the following:

- LAW no. 13 of 09/01/89
- MINISTRY'S DECREE no. 236 of 14/06/89
- UNI STD. 9801
- MACHINE DIRECTIVE D.P.R. 24 July 1996, no. 459 - 98/37/EEC - 98/79/EEC (89/392/EEC - 91/368/EEC - 93/44/EEC - 93/68/EEC)
- ELECTROMAGNETIC COMPATIBILITY DIRECTIVE D.L. 12 November 1996, no. 615 - 89/336/EEC - 92/31/EEC - 93/68/EEC - 93/97/EEC
- LOW VOLTAGE DIRECTIVE Law no. 791 del 77, D. L. no. 626 of 96 - 73/23/EEC - 93/68/EEC

* The sizes given may vary depending on the shape of the stairs.



FABOC DUE s.r.l.

Via Toscana, 148
50052 CERTALDO (Fi) - Italy
Tel. 0571 662474 - Fax 0571 666865
E-mail: info@fabocdue.it - www.fabocdue.it

Local Agent

• We reserve the right implement modification without notice.